

Bulkwholesale Australia Pre - Wash Spotter

Bulkwholesale Australia

Chemwatch: 4789-82

Version No: 2.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 1

Issue Date: 27/06/2017 Print Date: 31/01/2018 S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Pre - Wash Spotter		
Synonyms	Not Available		
Other means of identification	Not Available		
Relevant identified uses of the substance or mixture and uses advised against			

Relevant identified uses Pre-wash spotting solution.

Details of the supplier of the safety data sheet

Registered company name	Bulkwholesale Australia
Address	2/7 Commercial Court, Tullamarine VIC 3043
Telephone	1300 096 435
Website	https://www.bulkwholesale.com.au/
Email	orders@bulkwholesale.com.au

Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substature Poisons Schedule Not Applicable Classification Not Applicable Label elements Hazard pictogram(s) Not Applicable SIGNAL WORD NOT APPLICABLE

Hazard statement(s)

Not Applicable

Precautionary statement(s) Prevention
Not Applicable

Precautionary statement(s) Response Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name	
Not Available	1-10	NV Chemicals Pre - Wash Spotter	
1300-72-7	1-10	sodium xylenesulfonate	
111-76-2	1-10	ethylene glycol monobutyl ether	
Not Available	1-10	nonyl phenol ethoxylate	
Not Available	<0.1	preservative	
7732-18-5	>60	water	

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For acute or short term repeated exposures to ethylene glycol:

- Early treatment of ingestion is important. Ensure emesis is satisfactory.
- Test and correct for metabolic acidosis and hypocalcaemia.
- Apply sustained diuresis when possible with hypertonic mannitol.
- Evaluate renal status and begin haemodialysis if indicated. [I.L.O]
- Rapid absorption is an indication that emesis or lavage is effective only in the first few hours. Cathartics and charcoal are generally not effective.
- Correct acidosis, fluid/electrolyte balance and respiratory depression in the usual manner. Systemic acidosis (below 7.2) can be treated with intravenous sodium bicarbonate solution.
- Ethanol therapy prolongs the half-life of ethylene glycol and reduces the formation of toxic metabolites.
- Pyridoxine and thiamine are cofactors for ethylene glycol metabolism and should be given (50 to 100 mg respectively) intramuscularly, four times per day for 2 days.
- Magnesium is also a cofactor and should be replenished. The status of 4-methylpyrazole, in the treatment regime, is still uncertain. For clearance of the material and its metabolites, haemodialysis is much superior to peritoneal dialysis.

[Ellenhorn and Barceloux: Medical Toxicology]

It has been suggested that there is a need for establishing a new biological exposure limit before a workshift that is clearly below 100 mmol ethoxy-acetic acids per mole creatinine in morning urine of people occupationally exposed to ethylene glycol ethers. This arises from the finding that an increase in urinary stones may be associated with such exposures. Laitinen J., et al: Occupational & Environmental Medicine 1996; 53, 595-600

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.			
Advice for firefighters				
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. 			
Fire/Explosion Hazard	 Non combustible. Not considered a significant fire risk, however containers may burn. Decomposition may produce toxic fumes of: , phosphorus oxides (POx) , sulfur oxides (SOx) May emit poisonous fumes. May emit corrosive fumes. 			
HAZCHEM	Not Applicable			

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Environmental hazard - contain spillage. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite.
Major Spills	 Environmental hazard - contain spillage. Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT allow clothing wet with material to stay in contact with skin
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers.
Conditions for safe storage,	including any incompatibilities
Suitable container	Polyethylene or polypropylene container. Packing as recommended by manufacturer.

Check all containers are clearly labelled and free from leaks.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

None known

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

Storage incompatibility

INGREDIENT DATA									
Source	Ingredient	Material name	TWA		STEL		Peak		Notes
Australia Exposure Standards	ethylene glycol monobutyl ether	2-Butoxyethanol	96.9 mg/m3 / 20	0 ppm	242 mg/m3 /	50 ppm	Not Availabl	е	Not Available
EMERGENCY LIMITS									
Ingredient	Material name			TEEL-1 TEE		TEEL-2	-2 TE		L-3
ethylene glycol monobutyl ether	Butoxyethanol, 2-; (Glycol ether EB)	Butoxyethanol, 2-; (Glycol ether EB)			60 ppm 120 ppm		700 ppm		
Ingredient	Original IDLH			Revised IDLH					
NV Chemicals Pre - Wash Spotter	Not Available			Not Available					
sodium xylenesulfonate	Not Available			Not Available					
ethylene glycol monobutyl ether	700 ppm	700 ppm			Not Available				
nonyl phenol ethoxylate	Not Available			Not Available					
preservative	Not Available	Not Available			Not Available				
water	Not Available			Not Available					

Exposure controls

Appropriate engine

	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be
	highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
ngineering	The basic types of engineering controls are:
controls	Process controls which involve changing the way a job activity or process is done to reduce the risk.

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Pre - Wash Spotter

Personal protection	
Eye and face protection	 Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care.
Body protection	See Other protection below
Other protection	 Overalls. P.V.C. apron. Barrier cream.
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

NV Chemicals Pre - Wash Spotter

Material	CPI
BUTYL	С
NAT+NEOPR+NITRILE	С
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE	С
NEOPRENE/NATURAL	С
NITRILE	С
PE	С
PE/EVAL/PE	С
PVA	С
PVC	С
SARANEX-23	С
TEFLON	С
VITON	С

Respiratory protection

Type BAX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	BAX-AUS	-	BAX-PAPR-AUS / Class 1
up to 50 x ES	-	BAX-AUS / Class 1	-
up to 100 x ES	-	BAX-2	BAX-PAPR-2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

* CPI - Chemwatch	Performance	Index
-------------------	-------------	-------

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Alkaline liquid; mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	9.2	Decomposition temperature	Not Available

Pre - Wash Spotter

Initial boiling point and boiling range (°C)Not AvailableMolecular weight (g/mol)Not ApplicableFlash point (°C)Not AvailableTasteNot AvailableFuaporation rateNot AvailableExplosive propertiesNot AvailableFlammabilityNot AvailableOxidising propertiesNot AvailableUpper Explosive Limit (%)Not AvailableSurface Tension (dyn/cm or mN/m)Not AvailableLower Explosive Limit (%)Not AvailableVolatile Component (%vol)Not AvailableVapour pressure (kPa)Not AvailableOtatile Component (%vol)Not AvailableSolubility in water (g/L)MisciblepH as a solution (1%)Not Available	Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Evaporation rateNot AvailableExplosive propertiesNot AvailableFlammabilityNot AvailableOxidising propertiesNot AvailableUpper Explosive Limit (%)Not AvailableSurface Tension (dyn/cm or mN/m)Not AvailableLower Explosive Limit (%)Not AvailableVolatile Component (%vol)Not AvailableVapour pressure (kPa)Not AvailableGas groupNot AvailableSolubility in water (g/L)MisciblePH as a solution (1%)Not Available	• • • •	Not Available	Molecular weight (g/mol)	Not Applicable
FlammabilityNot AvailableOxidising propertiesNot AvailableUpper Explosive Limit (%)Not AvailableSurface Tension (dyn/cm or mN/m)Not AvailableLower Explosive Limit (%)Not AvailableVolatile Component (%vol)Not AvailableVapour pressure (kPa)Not AvailableGas groupNot AvailableSolubility in water (g/L)MisciblePH as a solution (1%)Not Available	Flash point (°C)	Not Available	Taste	Not Available
Upper Explosive Limit (%)Not AvailableSurface Tension (dyn/cm or mN/m)Not AvailableLower Explosive Limit (%)Not AvailableVolatile Component (%vol)Not AvailableVapour pressure (kPa)Not AvailableGas groupNot AvailableSolubility in water (g/L)MisciblePH as a solution (1%)Not Available	Evaporation rate	Not Available	Explosive properties	Not Available
Upper Explosive Limit (%) Not Available Not Available Lower Explosive Limit (%) Not Available Volatile Component (%vol) Not Available Vapour pressure (kPa) Not Available Gas group Not Available Solubility in water (g/L) Miscible pH as a solution (1%) Not Available	Flammability	Not Available	Oxidising properties	Not Available
Vapour pressure (kPa) Not Available Gas group Not Available Solubility in water (g/L) Miscible pH as a solution (1%) Not Available	Upper Explosive Limit (%)	Not Available		Not Available
Solubility in water (g/L) Miscible pH as a solution (1%) Not Available	Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
	Vapour pressure (kPa)	Not Available	Gas group	Not Available
	Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
vapour density (Air = 1) NOT Available VOC g/L NOT Available	Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Not normally a hazard due to non-volatile nature of product		
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.		
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.		
Eye	There is some evidence to suggest that this material can cause	e eye irritation and damage in some persons.	
Chronic	There is some evidence that inhaling this product is more likely. There is limited evidence that, skin contact with this product is population. There is some evidence from animal testing that exposure to the Based on experience with similar materials, there is a possibility other toxic effects.	ay cause some concern following repeated or long-term occupational exposure. y to cause a sensitisation reaction in some persons compared to the general population. more likely to cause a sensitisation reaction in some persons compared to the general his material may result in toxic effects to the unborn baby. ty that exposure to the material may reduce fertility in humans at levels which do not cause r mutations, but there is not enough data to make an assessment.	
NV Chemicals Pre - Wash	ΤΟΧΙΟΙΤΥ	IRRITATION	
Spotter	Not Available	Not Available	
	тохісіту	IRRITATION	
sodium xylenesulfonate	Dermal (rabbit) LD50: >=2000 mg/kg ^[1]	Not Available	
	Oral (rat) LD50: >=3346 mg/kg ^[1]		
	тохісіту	IRRITATION	
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit): 100 mg SEVERE	
ethylene glycol monobutyl ether	Inhalation (rat) LC50: 449.48655 mg/l/4H ^[2]	Eye (rabbit): 100 mg/24h-moderate	
	Oral (rat) LD50: 250 mg/kg ^[2]	Skin (rabbit): 500 mg, open; mild	
	тохісіту	IRRITATION	
water	Not Available	Not Available	

NV Chemicals Pre - Wash Spotter	Not available.		
SODIUM XYLENESULFONATE	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. For alkyl sulfates; alkane sulfonates and alpha-olefin sulfonates Most chemicals of this category are not defined substances, but mixtures of homologues with different alkyl side chains. Common physical and/or biological pathways result in structurally similar breakdown products, and are, together with the surfactant properties, responsible for similar environmental behavior and essentially identical hazard profiles with regard to human health. Acute toxicity: These substances are well absorbed after ingestion; penetration through the skin is however, poor. After absorption, these chemicals are distributed mainly to the liver. Toxicological data is available and well documented for representative toluene, xylene and cumene sulfonates (including sodium, potassium, ammounium and calcium salts). These data show that hydrotropes have low toxicity for all routes, do not cause genetic damage, show no evidence of causing cancer in long-term skin studies, and have not caused birth defects, developmental defects or reduced fertility.		
	The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. For ethylene glycol monoalkyl ethers and their acetates (EGMAEs): Typical members of this category are ethylene glycol propylene ether (EGPE), ethylene glycol butyl ether (EGBE) and ethylene glycol hexyl ether (EGHE) and their acetates. EGMAEs are substrates for alcohol dehydrogenase isozyme ADH-3, which catalyzes the conversion of their terminal alcohols to aldehydes (which are transient metabolites). Further, rapid conversion of the aldehydes by aldehyde dehydrogenase produces alkoxyacetic acids, which are the predominant urinary metabolites of mono substituted glycol thers. Acute Toxicity: Oral LD50 values in rats for all category members range from 739 (EGHE) to 3089 mg/kg bw (EGPE), with values increasing with decreasing molecular weight. Animal testing showed that exposure to ethylene glycol monobutyl ether resulted in toxicity to both the mother and the embryo. Reproductive effects were thought to be less than that of other monoalkyl ethers of ethylene glycol. Chronic exposure may cause anaemia, with enlargement and fragility of red blood cells. It is thought that in animals butoxyethanol may cause generalized cloting and bone infarction. For ethylene glycol: Ethylene glycol: Ethylene glycol: Ethylene glycol: Ethylene glycol is quickly and extensively absorbed throughout the gastrointestinal tract. Limited information suggests that it is also absorbed through the airways; absorption through skin is apparently slow. Following absorption, it is distributed throughout the body. In humans, it is initially metabolized by alcohol dehydrogenase to form glycoaldehyde, which is rapidly converted to glycolic acid and glyoxal. NOTE: Changes in kidney, liver		
ETHYLENE GLYCOL MONOBUTYL ETHER	urinary metabolites of mono substituted glycol ethers. Acute Toxicity: Oral LD50 values in rats for all category members range from 739 (EGHE) to 3 decreasing molecular weight. Animal testing showed that exposure to ethylene glycol monobutyl ether resulted in toxicity to both thought to be less than that of other monoalkyl ethers of ethylene glycol. Chronic exposure may cause anaemia, with enlargement and fragility of red blood cells. It is thou clotting and bone infarction. For ethylene glycol: Ethylene glycol is quickly and extensively absorbed throughout the gastrointestinal tract. Limited airways; absorption through skin is apparently slow. Following absorption, it is distributed throug alcohol dehydrogenase to form glycoaldehyde, which is rapidly converted to glycolic acid and gly	089 mg/kg bw (EGPE), with values increasing with the mother and the embryo. Reproductive effects were ight that in animals butoxyethanol may cause generalized information suggests that it is also absorbed through the hout the body. In humans, it is initially metabolized by oxal.	
	urinary metabolites of mono substituted glycol ethers. Acute Toxicity: Oral LD50 values in rats for all category members range from 739 (EGHE) to 3 decreasing molecular weight. Animal testing showed that exposure to ethylene glycol monobutyl ether resulted in toxicity to both thought to be less than that of other monoalkyl ethers of ethylene glycol. Chronic exposure may cause anaemia, with enlargement and fragility of red blood cells. It is thou clotting and bone infarction. For ethylene glycol: Ethylene glycol: Ethylene glycol is quickly and extensively absorbed throughout the gastrointestinal tract. Limitec airways; absorption through skin is apparently slow. Following absorption, it is distributed throug alcohol dehydrogenase to form glycoaldehyde, which is rapidly converted to glycolic acid and gly NOTE: Changes in kidney, liver, spleen and lungs are observed in animals exposed to high con	089 mg/kg bw (EGPE), with values increasing with the mother and the embryo. Reproductive effects were ight that in animals butoxyethanol may cause generalized information suggests that it is also absorbed through the hout the body. In humans, it is initially metabolized by oxal.	
MONOBUTYL ETHER	urinary metabolites of mono substituted glycol ethers. Acute Toxicity: Oral LD50 values in rats for all category members range from 739 (EGHE) to 3 decreasing molecular weight. Animal testing showed that exposure to ethylene glycol monobutyl ether resulted in toxicity to both thought to be less than that of other monoalkyl ethers of ethylene glycol. Chronic exposure may cause anaemia, with enlargement and fragility of red blood cells. It is thou clotting and bone infarction. For ethylene glycol: Ethylene glycol is quickly and extensively absorbed throughout the gastrointestinal tract. Limited airways; absorption through skin is apparently slow. Following absorption, it is distributed throug alcohol dehydrogenase to form glycoaldehyde, which is rapidly converted to glycolic acid and gly. NOTE: Changes in kidney, liver, spleen and lungs are observed in animals exposed to high con SDS	089 mg/kg bw (EGPE), with values increasing with the mother and the embryo. Reproductive effects were ight that in animals butoxyethanol may cause generalized information suggests that it is also absorbed through the hout the body. In humans, it is initially metabolized by oxal.	
MONOBUTYL ETHER SODIUM XYLENESULFONATE & WATER	urinary metabolites of mono substituted glycol ethers. Acute Toxicity: Oral LD50 values in rats for all category members range from 739 (EGHE) to 3 decreasing molecular weight. Animal testing showed that exposure to ethylene glycol monobutyl ether resulted in toxicity to both thought to be less than that of other monoalkyl ethers of ethylene glycol. Chronic exposure may cause anaemia, with enlargement and fragility of red blood cells. It is thou- clotting and bone infarction. For ethylene glycol: Ethylene glycol: Ethylene glycol is quickly and extensively absorbed throughout the gastrointestinal tract. Limitec airways; absorption through skin is apparently slow. Following absorption, it is distributed throug alcohol dehydrogenase to form glycoaldehyde, which is rapidly converted to glycolic acid and gly NOTE: Changes in kidney, liver, spleen and lungs are observed in animals exposed to high con SDS	1089 mg/kg bw (EGPE), with values increasing with a the mother and the embryo. Reproductive effects were light that in animals butoxyethanol may cause generalized linformation suggests that it is also absorbed through the hout the body. In humans, it is initially metabolized by oxal. centrations of this substance by all routes. ** ASCC (NZ)	
MONOBUTYL ETHER SODIUM XYLENESULFONATE & WATER Acute Toxicity	urinary metabolites of mono substituted glycol ethers. Acute Toxicity: Oral LD50 values in rats for all category members range from 739 (EGHE) to 3 decreasing molecular weight. Animal testing showed that exposure to ethylene glycol monobutyl ether resulted in toxicity to both thought to be less than that of other monoalkyl ethers of ethylene glycol. Chronic exposure may cause anaemia, with enlargement and fragility of red blood cells. It is thou clotting and bone infarction. For ethylene glycol: Ethylene glycol: Ethylene glycol is quickly and extensively absorbed throughout the gastrointestinal tract. Limitec airways; absorption through skin is apparently slow. Following absorption, it is distributed through alcohol dehydrogenase to form glycoaldehyde, which is rapidly converted to glycolic acid and gly NOTE: Changes in kidney, liver, spleen and lungs are observed in animals exposed to high con SDS No significant acute toxicological data identified in literature search. Carcinogenicity	089 mg/kg bw (EGPE), with values increasing with a the mother and the embryo. Reproductive effects were aght that in animals butoxyethanol may cause generalized l information suggests that it is also absorbed through the hout the body. In humans, it is initially metabolized by oxal.	
MONOBUTYL ETHER SODIUM XYLENESULFONATE & WATER Acute Toxicity Skin Irritation/Corrosion	urinary metabolites of mono substituted glycol ethers. Acute Toxicity: Oral LD50 values in rats for all category members range from 739 (EGHE) to 3 decreasing molecular weight. Animal testing showed that exposure to ethylene glycol monobutyl ether resulted in toxicity to bott thought to be less than that of other monoalkyl ethers of ethylene glycol. Chronic exposure may cause anaemia, with enlargement and fragility of red blood cells. It is thou clotting and bone infarction. For ethylene glycol is quickly and extensively absorbed throughout the gastrointestinal tract. Limited airways; absorption through skin is apparently slow. Following absorption, it is distributed throug alcohol dehydrogenase to form glycoaldehyde, which is rapidly converted to glycolic acid and gly NOTE: Changes in kidney, liver, spleen and lungs are observed in animals exposed to high con SDS No significant acute toxicological data identified in literature search. Carcinogenicity Reproductivity	089 mg/kg bw (EGPE), with values increasing with a the mother and the embryo. Reproductive effects were ight that in animals butoxyethanol may cause generalized information suggests that it is also absorbed through the hout the body. In humans, it is initially metabolized by oxal. centrations of this substance by all routes. ** ASCC (NZ)	

Legend:

🗙 – Data available but does not fill the criteria for classification Data available to make classification

O – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

NV Chemicals Pre - Wash Spotter	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>=1580mg/L	2
sodium xylenesulfonate	EC50	48	Crustacea	>400mg/L	1
	EC50	96	Algae or other aquatic plants	>=758mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	1250mg/L	4
ethylene glycol monobutyl ether	EC50	48	Crustacea	>1000mg/L	4
	NOEC	96	Crustacea	1000mg/L	4
water	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE

Pre - Wash Spotter

(Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

On the basis of available evidence concerning either toxicity, persistence, potential to accumulate and or observed environmental fate and behaviour, the material may present a danger, immediate or long-term and /or delayed, to the structure and/ or functioning of natural ecosystems. **DO NOT** discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethylene glycol monobutyl ether	LOW (Half-life = 56 days)	LOW (Half-life = 1.37 days)
water	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation	
ethylene glycol monobutyl ether	LOW (BCF = 2.51)	
water	LOW (LogKOW = -1.38)	

Mobility in soil

Ingredient	Mobility
ethylene glycol monobutyl ether	HIGH (KOC = 1)
water	LOW (KOC = 14.3)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: Preduction Recycling Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material). Decontaminate empty containers.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

NV CHEMICALS PRE - WASH SPOTTER(NOT APPLICABLE) IS FOUND ON THE FOLLOWING REGULATORY LISTS Not Applicable

SODIUM XYLENESULFONATE(1300-72-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Substances Information System - Consolidated Lists

ETHYLENE GLYCOL MONOBUTYL ETHER(111-76-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

Australia Inventory of Chemical Substances (AICS)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

WATER(7732-18-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

National Inventory	Status
Australia - AICS	Υ
Canada - DSL	Υ
Canada - NDSL	N (water; sodium xylenesulfonate; ethylene glycol monobutyl ether)
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	Υ
Japan - ENCS	Υ
Korea - KECI	Υ
New Zealand - NZIoC	Υ
Philippines - PICCS	Υ
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

Name	CAS No
sodium xylenesulfonate	1300-72-7, 30587-85-0

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chernwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average PC – STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit_o. IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL : No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.