

Bulk Blendz Cutlery Cleaner Bulkwholesale Australia Pty Ltd Chemwatch: 5423-78

Version No: 2.1

Chemwatch Hazard Alert Code: 3

lssue Date: **14/09/2020** Print Date: **12/05/2022** L.GHS.AUS.EN.E

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Product Identifier		
Product name	Bulk Blendz Cutlery Cleaner	
Chemical Name	Not Applicable	
Synonyms	Not Available	
Proper shipping name	OXIDISING LIQUID, CORROSIVE, N.O.S. (contains sodium perchlorate and sodium dichloroisocyanurate)	
Chemical formula	Not Applicable	
Other means of identification	Not Available	

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Use according to manufacturer's directions.

Details of the supplier of the safety data sheet

Registered company name	Bulkwholesale Australia Pty Ltd	Re-Stox Business Supplies & Ranges Coffee
Address	2/7 Commercial Court, Tullamarine VIC 3043 Australia	14 Melba Avenue Victoria 3140 Australia
Telephone	1300 096 435	+61 39738 7730
Fax		Not Available
Website	https://www.bulkwholesale.com.au	
Email	orders@bulkwholesale.com.au	gwilliams@restox.com.au

Emergency telephone number

Association / Organisation	N.V.Chemicals(Aust) P/L	Re-Stox Business Supplies & Ranges Coffee
Emergency telephone numbers	0411 387 097	+61 409 866 355
Other emergency telephone numbers	Not Available	Not Available

SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

ChemWatch Hazard Ratings



Legend: 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements		
Hazard pictogram(s)		
Signal word	Danger	
Hazard statement(s)		
H314	Causes severe skin burns and eye damage.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H411	Toxic to aquatic life with long lasting effects.	
H272	May intensify fire; oxidiser.	

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P260	Do not breathe mist/vapours/spray.	
P264	Wash all exposed external body areas thoroughly after handling.	
P271	Use only outdoors or in a well-ventilated area.	
P280	Wear protective gloves, protective clothing, eye protection and face protection.	
P220	Keep away from clothing and other combustible materials.	
P273	Avoid release to the environment.	

Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/physician/first aider.
P370+P378	In case of fire: Use alcohol resistant foam or fine spray/water fog to extinguish.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
497-19-8	>60	sodium carbonate
7758-29-4	<10	sodium tripolyphosphate
7601-89-0	<10	sodium perchlorate
7757-82-6	<10	sodium sulfate
2893-78-9	<10	sodium dichloroisocyanurate
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4.	

Classification drawn from C&L; * EU IOELVs available

SECTION 4 First aid measures

Eye Contact	 If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor. Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested. Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

For acute or short-term repeated exposures to highly alkaline materials:

Respiratory stress is uncommon but present occasionally because of soft tissue edema.

• Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary.

- Oxygen is given as indicated.
- The presence of shock suggests perforation and mandates an intravenous line and fluid administration.
- Damage due to alkaline corrosives occurs by liquefaction necrosis whereby the saponification of fats and solubilisation of proteins allow deep penetration into the tissue.
- Alkalis continue to cause damage after exposure.

INGESTION:

Milk and water are the preferred diluents

No more than 2 glasses of water should be given to an adult.

- Neutralising agents should never be given since exothermic heat reaction may compound injury.
- * Catharsis and emesis are absolutely contra-indicated.
- * Activated charcoal does not absorb alkali.

* Gastric lavage should not be used.

- Supportive care involves the following:
- Withhold oral feedings initially.
- If endoscopy confirms transmucosal injury start steroids only within the first 48 hours.
- Carefully evaluate the amount of tissue necrosis before assessing the need for surgical intervention.
 Patients should be instructed to seek medical attention whenever they develop difficulty in swallowing (dysphagia).
- SKIN AND EYE:

Injury should be irrigated for 20-30 minutes.

Eye injuries require saline. [Ellenhorn & Barceloux: Medical Toxicology]

SECTION 5 Firefighting measures

Extinguishing media

FOR SMALL FIRE:

USE FLOODING QUANTITIES OF WATER.

DO NOT use dry chemical, CO2, foam or halogenated-type extinguishers.

FOR LARGE FIRE

Flood fire area with water from a protected position

Special hazards arising from the substrate or mixture

Fire Incompatibility	 Avoid storage with reducing agents. Avoid any contamination of this material as it is very reactive and any contamination is potentially hazardous 	
Advice for firefighters		

Auvice for menginers		
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water courses. Fight fire from a safe distance, with adequate cover. Extinguishers should be used only by trained personnel. Use water delivered as a fine spray to control fire and cool adjacent area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. 	

	 If safe to do so, remove containers from path of fire. If fire gets out of control withdraw personnel and warn against entry. Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	 Will not burn but increases intensity of fire. May explode from friction, shock, heat or containment. Heating may cause expansion or decomposition leading to violent rupture of containers. Heat affected containers remain hazardous. Contact with combustibles such as wood, paper, oil or finely divided metal may produce spontaneous combustion or violent decomposition. May emit irritating, poisonous or corrosive fumes. Combustion/decomposition may produce acrid/toxic fumes of carbon monoxide (CO). Decomposes on heating and produces toxic fumes of: carbon dioxide (CO2) hydrogen chloride phosgene nitrogen oxides (NOX) other pyrolysis products typical of burning organic material.
HAZCHEM	2W

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Environmental hazard - contain spillage. Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material. Check regularly for spills and leaks. Clean up all spills immediately. No smoking, naked lights, ignition sources. Avoid all contact with any organic matter including fuel, solvents, sawdust, paper or cloth and other incompatible materials, as ignition may result. Avoid breathing dust or vapours and all contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with dry sand, earth, inert material or vermiculite. DO NOT use sawdust as fire may result. Scoop up solid residues and seal in labelled drums for disposal. Neutralise/decontaminate area.
Major Spills	 Environmental hazard - contain spillage. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water courses. No smoking, flames or ignition sources. Increase ventilation. Contain spill with sand, earth or other clean, inert materials. NEVER USE organic absorbents such as sawdust, paper or cloth. Use spark-free and explosion-proof equipment. Collect any recoverable product into labelled containers for possible recycling. Avoid contamination with organic matter to prevent subsequent fire and explosion. DO NOT mix fresh with recovered material. Collect residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. Decontamination of drains or waterways occurs advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling	
Safe handling	 DO NOT allow clothing wet with material to stay in contact with skin For oxidisers, including peroxides. Avoid personal contact and inhalation of dust, mist or vapours. Provide adequate ventilation. Always wear protective equipment and wash off any spillage from clothing. Keep material away from light, heat, flammables or combustibles. Keep cool, dry and away from incompatible materials. Avoid physical damage to containers. DO NOT repack or return unused portions to original containers. Withdraw only sufficient amounts for immediate use. Use only minimum quantity required. Avoid using solutions of peroxides in volatile solvents. Solvent evaporation should be controlled to avoid dangerous concentration of the peroxide. Do NOT allow oxidisers to contact iron or compounds of iron, cobalt, or copper, metal oxide salts, acids or bases. Do NOT use metal spatulas to handle oxidisers Do NOT use glass containers with screw cap lids or glass stoppers. Store peroxides at the lowest possible temperature, consistent with their solubility and freezing point.

	 CAUTION: Do NOT store liquids or solutions of peroxides at a temperature below that at which the oxidiser freezes or precipitates. Peroxides, in particular, in this form are extremely shock and heat-sensitive. Refrigerated storage of peroxides must ONLY be in explosion-proof units. The hazards and consequences of fires and explosions during synthesis and use of oxidisers is widely recognised; spontaneous or induced decomposition may culminate in a variety of ways, ranging from moderate gassing to spontaneous ignition or explosion. The heat released from spontaneous decomposition of an energy-rich compound causes a rise in the surrounding temperature; the temperature will rise until thermal balance is established or until the material heats to decomposition, The most effective means for minimising the consequences of an accident is to limit quantities to a practical minimum. Even gram-scale explosions can be serious. Once ignited the burning of peroxides cannot be controlled and the area should be evacuated. Unless there is compelling reason to do otherwise, peroxide concentration should be limited to 10% (or less with vigorous reactants). Peroxide concentration is rarely as high as 1% in the reaction mixture of polymerisation or other free-radical reactions, Oxidisers to the hot monomer is extremely dangerous. A violent reaction (e.g., fire or explosion) can result from inadvertent mixing of promoters (frequently used with peroxides in polymerisation systems) with full-strength oxidisers Organic peroxides and many varieties of dust and dirt). This can initiate rapid, uncontrolled decomposition of peroxides and possible generation of intense heat, fire or explosion The consequences of accidental contamination from returning withdrawn material to the storage container can be disastrous. When handling NEVER smoke, eat or drink. Always wash hands with soap and water after handling. Use only good occupational work practice. Obs
Other information	 Store in original containers. Keep containers securely sealed as supplied. Store in a cool, well ventilated area. Keep dry. Store under cover and away from sunlight. Store away from flammable or combustible materials, debris and waste. Contact may cause fire or violent reaction. Store away from incompatible materials and foodstuff containers. DO NOT stack on wooden floors or pallets. Protect containers from physical damage. Check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS. In addition, Goods of Class 5.1, packing group II should be: stored in piles so that the height of the pile does not exceed 1 metre the maximum quantity in a pile or building does not exceed 1000 tonnes unless the area is provided with automatic fire extinguishers or 3 meters if not. the minimum distance between piles is not less than 2 metres where the room is provided with automatic fire extinguishers or 3 meters if not. the minimum distance to walls is not less than 1 metre.
Conditions for safe storage, in	cluding any incompatibilities
	For low viscosity materials

Suitable container	 Skg/ 20kg bulk. For low viscosity materials Drums and jerricans must be of the non-removable head type. Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids: Removable head packaging and cans with friction closures may be used. Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages *. In addition, where inner packagings are glass and contain liquids of packing group I and II there must be sufficient inert absorbent to absorb any spillage *.
	* unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.
Storage incompatibility	 Avoid reaction with oxidising agents, bases and strong reducing agents. Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.
	•

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3	
sodium carbonate	7.6 mg/m3	83 mg/m3		500 mg/m3	
sodium tripolyphosphate	0.61 mg/m3	6.8 mg/m3		620 mg/m3	
sodium perchlorate	6.3 mg/m3	69 mg/m3		420 mg/m3	
sodium perchlorate	3.8 mg/m3	41 mg/m3		250 mg/m3	
sodium sulfate	9.8 mg/m3	110 mg/m3		650 mg/m3	
				1	
Ingredient	Original IDLH		Revised IDLH		
sodium carbonate	Not Available		Not Available	lot Available	
sodium tripolyphosphate	Not Available		Not Available		
sodium perchlorate	Not Available		Not Available		
sodium sulfate	Not Available		Not Available		

Ingredient	Original IDLH Revised IDLH			
sodium dichloroisocyanurate	Not Available	Not Available		
Occupational Exposure Banding				
	Occupational Exposure Pand Pating	Occupational Exposure Band Limit		
sodium tripolypnosphate	E	≤ 0.01 mg/m ²		
	E	≤ 0.01 mg/m ²		
sodium sulfate	E	≤ 0.01 mg/m³		
sodium dichloroisocyanurate	E ≤ 0.01 mg/m ³			
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.			
MATERIAL DATA				
Exposure controls				
	Engineering controls are used to treated of place a be highly effective in protecting workers and will typically be i The basic types of engineering controls are: Process controls which involve changing the way a job activit Enclosure and/or isolation of emission source which keeps a "adds" and "removes" air in the work environment. Ventilatior ventilation system must match the particular process and che Employers may need to use multiple types of controls to prev General exhaust is adequate under normal operating condition overexposure exists, wear approved respirator. Correct fit is or closed storage areas. Air contaminants generated in the w velocities" of fresh circulating air required to effectively remove Type of Contaminant:	y or process is done to reduce the risk. selected hazard "physically" away from the worker and ven a can remove or dilute an air contaminant if designed proper mical or contaminant in use. vent employee overexposure. ons. Local exhaust ventilation may be required in specific di essential to obtain adequate protection. Provide adequate v orkplace possess varying "escape" velocities which, in turn re the contaminant.	of protection. tilation that strategically ly. The design of a cumstances. If risk of entilation in warehouse , determine the "capture	
			0.25.0.5 m/s	
	solvent, vapours, degreasing etc., evaporating from tank (in still air).			
Appropriate engineering	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) 0.5-1 m/s (100-200 f/min.)			
controls	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) f/min.)			
	grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion). 2.5-10 m/s (500-2000 f/min.)			
	Within each range the appropriate value depends on:			
	Lower end of the range	Upper end of the range		
	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents		
	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity		
	3: Intermittent, low production.	3: High production, heavy use		
	4: Large hood or large air mass in motion	4: Small hood-local control only		
	Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.			
Personal protection				
Eye and face protection	 Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or an environment only after workers have washed hands thoroughly. 			
Skin protection	See Hand protection below			
	Elbow length PVC gloves			
Hands/feet protection	When handling corrosive liquids, wear trousers or overal The selection of suitable gloves does not only depend on the manufacturer. Where the chemical is a preparation of severa and has therefore to be checked prior to the application.	s outside of boots, to avoid spills entering boots. material, but also on further marks of quality which vary fro I substances, the resistance of the glove material can not be	m manufacturer to e calculated in advance	

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be

washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

alaman alamé any sua ang lugun anéané és séana in éla

Bulk Blendz Cutlery Cleaner

	 Sintability and duability of glove type is dependent on disage. Important factors in the selection of gloves include. frequency and duration of contact, chemical resistance of glove material, glove thickness and dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as: Excellent when breakthrough time > 480 min Good when breakthrough time < 20 min Foor general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove of varying thickness may be required for specific tasks. For example: Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only filely to give short duration protection and would normally be just for single us
	 Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Body protection	See Other protection below
Other protection	 Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Eyewash unit. Ensure there is ready access to a safety shower. Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets). Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return.

Recommended material(s) **GLOVE SELECTION INDEX**

Respiratory protection

Type ABK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Glove selection is based on a modified presentation of the: "Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computergenerated selection:

Cutlery Cleaner

Material	СРІ
NATURAL RUBBER	A
NITRILE	A

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted

Selection of the Class and Type of respirator will depend upon the level of breathing

zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	ABK-AUS / Class1 P2	-
up to 50	1000	-	ABK-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	ABK-2 P2
up to 100	10000	-	ABK-3 P2
100+			Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Appearance	White solid with a slight odour; mixes with water.				
Physical state	Liquid	Relative density (Water = 1)	Not Available		
Odour	Not Available	Partition coefficient n-octanol / water	Not Available		
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available		
pH (as supplied)	11.5	Decomposition temperature	Not Available		
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available		
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable		
Flash point (°C)	Not Applicable	Taste	Not Available		
Evaporation rate	Not Available	Explosive properties	Not Available		
Flammability	Not Applicable	Oxidising properties	Not Available		
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available		
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available		
Vapour pressure (kPa)	Not Available	Gas group	Not Available		
Solubility in water	Miscible	pH as a solution (Not Available%)	>11.5		
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available		

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable under normal handling conditions. Prolonged exposure to heat. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological ef	fects
Inhaled	Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful. Inhalation of alkaline corrosives may produce irritation of the respiratory tract with coughing, choking, pain and mucous membrane damage. Pulmonary oedema may develop in more severe cases; this may be immediate or in most cases following a latent period of 5-72 hours. Symptoms may include a tightness in the chest, dyspnoea, frothy sputum, cyanosis and dizziness. Findings may include hypotension, a weak and rapid pulse and moist rales. Inhalation of quantities of liquid mist may be extremely hazardous, even lethal due to spasm, extreme irritation of larynx and bronchi, chemical pneumonitis and pulmonary oedema. Chlorine vapour is extremely irritating to the upper respiratory tract and lungs Symptoms of exposure to chlorine include coughing, choking, breathing difficulty, chest pain, headache, vomiting, pulmonary oedema. Inhalation may cause lung congestion, bronchitis and loss of consciousness. Effects may be delayed. Delayed effects of exposure to chlorine vapour can include shortness of breath, violent headaches, pulmonary oedema and pneumonia. Earlier reports suggested that concentrations around 5 ppm chlorine caused respiratory complaints, corrosion of the teeth, inflammation of the mucous membranes of the nose and increased susceptibility to tuberculosis in chronically-exposed workers. Recent studies have not confirmed these findings. Concentrations too low to effect the lower respiratory tract may however irritate the eyes, nose and throat. Amongst 29 volunteers exposed at 0.5, 1 or 2 ppm chlorine for 4 to 8 hours the following responses were recorded: itching or burning of the nose, itching or burning of the throat, production of tears, urge to cough, runny nose, nausea, headache, general discomfort, dizziness, drowsiness and shortness of breath Symptoms of sodium carbonate inhalation may include coughing, sore throat, and laboured breathing. Severe or continued inhalation exp
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Ingestion of alkaline corrosives may produce immediate pain, and circumoral burns. Mucous membrane corrosive damage is characterised by a white appearance and soapy feel; this may then become brown, oedematous and ulcerated. Profuse salivation with an inability to swallow or speak may also result. Even where there is limited or no evidence of chemical burns, both the oesophagus and stomach may experience a burning pain; vomiting and diarrhoea may follow. The vomitus may be thick and may be slimy (mucous) and may eventually contain blood and shreds of mucosa. Epiglottal oedema may result in respiratory distress and asphyxia. Marked hypotension is symptomatic of shock; a weak and rapid pulse, shallow respiration and clammy skin may also be evident. Circulatory collapse may occur and, if uncorrected, may produce renal

	failure. Severe exposures may result in oesophageal or gastric perforation accompanied by mediastinitis, substernal pain, peritonitis, abdominal rigidity and fever. Although oesophageal, gastric or pyloric stricture may be evident initially, these may occur after weeks or even months and years. Death may be quick and results from asphyxia, circulatory collapse or aspiration of even minute amounts. Death may also be delayed as a result of perforation, pneumonia or the effects of stricture formation.
Skin Contact	The material can produce severe chemical burns following direct contact with the skin. Open cuts, abraded or irritated skin should not be exposed to this material Solution of material in moisture on the skin, or perspiration, may markedly increase skin corrosion and accelerate tissue destruction Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Contact with concentrated solutions of sodium carbonate may cause tissue damage "soda ulcers"
Eye	When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation. Direct contact with alkaline corrosives may produce pain and burns. Oedema, destruction of the epithelium, corneal opacification and iritis may occur. In less severe cases these symptoms tend to resolve. In severe injuries the full extent of the damage may not be immediately apparent with late complications comprising a persistent oedema, vascularisation and corneal scarring, permanent opacity, staphyloma, cataract, symblepharon and loss of sight. 510sodacarb Alkaline salts may be intensely irritating to the eyes and precautions should be taken to ensure direct eye contact is avoided.
Chronic	Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Gastrointestinal disturbances may also occur. Chronic exposures may result in dermatitis and/or conjunctivitis. Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems. Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. Serious damage (clear functional disturbance or morphological change which may have toxicological significance) is likely to be caused by repeated or prolonged exposure. As a rule the material produces, or contains a substance which produces serve lesions. Such damage may become apparent following direct application in subchronic (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity tests. On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment. Limited evidence shows that inhalation of the material is capable of inducing a sensitisation reaction in a significant number of individuals at a greater frequency than would be expected from the response of a normal population. Pulmonary sensitisation, resulting in hyperactive airway dysfunction and pulmonary allergy may be accompanied by fatigue, malaise and aching. Significant symptoms of exposure may persist for extended periods, even after exposure ceases. Symptoms can be activated by a variety of nonspecific environmental stimuli such as automobile exhaust, perfumes and passive smoking. Exposure to the material may cause concerns for humans owing to possible developmental toxic

Cutlery Cleaner	ΤΟΧΙΟΙΤΥ	IRRITATION
	Not Available	Not Available
	τοχιςιτγ	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[2]	Eye (rabbit): 100 mg/24h moderate
	Oral (Rat) LD50; 2800 mg/kg ^[2]	Eye (rabbit): 100 mg/30s mild
sodium carbonate		Eye (rabbit): 50 mg SEVERE
		Eye: adverse effect observed (irritating) ^[1]
		Skin (rabbit): 500 mg/24h mild
		Skin: no adverse effect observed (not irritating) $^{\left[1 \right]}$
	τοχιςιτγ	IRRITATION
	Dermal (rabbit) LD50: >3160 mg/kg ^[2]	Not Available
sodium tripolyphosphate	Inhalation(Rat) LC50; >0.39 mg/l4h ^[1]	
	Oral (Rat) LD50; >2000 mg/kg ^[1]	
	τοχιςιτγ	IRRITATION
sodium perchlorate	Oral (Rat) LD50; 2100 mg/kg ^[2]	Not Available
	тохісіту	IRRITATION
sodium sulfate	Inhalation(Rat) LC50; >2.4 mg/l4h ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50; >2000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
	ΤΟΧΙΟΙΤΥ	IRRITATION
	Dermal (rabbit) LD50: 6000 mg/kg ^[2]	Eye (rabbit): 10 mg/24hr-moderate
sodium dichloroisocyanurate	Inhalation(Rat) LC50; >0.27<1.17 mg/l4h ^[1]	Skin (rabbit) : Severe *
	Oral (Rat) LD50; 700 mg/kg ^[2]	

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise

	specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	
SODIUM CARBONATE	for sodium carbonate: Sodium carbonate has no or a low skin irritation potential but it is considered irritating to the the respiratory tract is also possible. No valid animal data are available on repeated dose toxicity studies by oral, dermal, inhalat repeated dose inhalation study, which was not reported in sufficient detail, revealed local eff the alkaline nature of the compound. Under normal handling and use conditions neither the the blood will be increased and therefore sodium carbonate is not expected to be systemica substance will neither reach the foetus nor reach male and female reproductive organs, whi toxicity and no risk for toxicity to reproduction. This was confirmed by a developmental stud test with bacteria was negative and based on the structure of sodium carbonate no genotox The material may cause skin irritation after prolonged or repeated exposure and may produ dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histolo spongy layer (spongiosis) and intracellular oedema of the epidermis.	eyes. Due to the alkaline properties an irritation of ion or by other routes for sodium carbonate. A fects on the lungs which could be expected based on concentration of sodium in the blood nor the pH of ally available in the body. It can be stated that the ich shows that there is no risk for developmental y with rabbits, rats and mice. An <i>in vitro</i> mutagenicity ic effects are expected. ce a contact dermatitis (nonallergic). This form of gically there may be intercellular oedema of the
SODIUM SULFATE	Equivocal Tumorigen by RTECS criteria. Reproductive effector in mice. for sodium sulfate: Sulfate (and sodium) ions are important constituents of the mammalian body and of natural foodstuffs and there is a considerable daily turnover of both ions (several grams/day expressed as sodium sulfate). Near-complete absorption of dietary sulfates may occur at low concentration, depending on the counter-ion, but absorption capacity can be saturated at higher artificial dosages resulting in cathartic effects. Absorption through skin can probably be ignored since sodium sulfate is fully ionised in solution. One source suggests that very high levels of sulfate in urine may occur due to absorption from dust inhalation. At dietary levels, excretion is mainly in the urine. Sulfates are found in all body cells, with highest concentrations in connective tissues, bone and cartilage. Sulfates play a role in several important metabolic pathways, including those involved in detoxification processes. The acute toxicity (LD50) of sodium sulfate has not been reliably established but is probably far in excess of 5000 mg/kg. In an inhalation study with an aerosol, no adverse effects were found at 10 mg/m3. Also human data indicate a very low acute toxicity of sodium sulfate. Human clinical experience indicates that very high oral doses of sodium sulfate, 300 mg/kg bw up to 20 grams for an adult, are well tolerated, except from (intentionally) causing severe diarrhoea. WHO/FAO did not set an ADI for sodium sulfate. There is no data on acute dermal toxicity, but this is probably of no concern because of total ionisation in solution. Sodium sulfate is not irritating to the skin and slightly irritating to the eyes. Respiratory irritation has never been reported. Based on wide practical experience with sodium sulfate, in combination with the natural occurrence of sulfate in the body, sensitising effects are highly unlikely. No suitable dermal and inhalation repeated-dose toxicity studies are available. Valid oral repeated dose toxicity studi	
SODIUM DICHLOROISOCYANURATE	Dermal (rabbit) LD50: 3160-5100 mg/kg * Manufacturer The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may produce severe skin irritation after prolonged or repeated exposure, and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) thickening of the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis. Prolonged contact is unlikely, given the severity of response, but repeated exposures may produce severe ulceration.	
SODIUM CARBONATE & SODIUM TRIPOLYPHOSPHATE & SODIUM SULFATE & SODIUM DICHLOROISOCYANURATE	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.	
Acute Toxicity	✓ Carcinogenicity	×
Skin Irritation/Corrosion	✓ Reproductivity	×
Serious Eye Damage/Irritation	✓ STOT - Single Exposure	×
Respiratory or Skin sensitisation	× STOT - Repeated Exposure	×
Mutagenicity	X Aspiration Hazard	×
	Legend: 🗙 – Data either n	ot available or does not fill the criteria for classification

Data entref flot available of does flot
 Data available to make classification

SECTION 12 Ecological information

Toxicity

Cutlery Cleaner	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
sodium carbonate	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	Not Available	Algae or other aquatic plants	1-10mg/l	2
	LC50	96h	Fish	300mg/l	2
	EC50	48h	Crustacea	156.6-298.9mg	1 4

	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50(ECx)	96h	Algae or other aquatic plants	69.2mg/l	2
sodium tripolyphosphate	EC50	48h	Crustacea	>70.7<101.3mg	1 2
	EC50	96h	Algae or other aquatic plants	69.2mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	48h	Fish	0.004mg/L	4
sodium perchlorate	LC50	96h	Fish	396.486-712.077mg	14
	EC50	72h	Algae or other aquatic plants	>435.7mg/l	2
	EC50	48h	Crustacea	>100mg/l	2
sodium sulfate	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	1h	Algae or other aquatic plants	0.011mg/L	4
	LC50	96h	Fish	ca.56-790mg/	1
	EC50	72h	Algae or other aquatic plants	1206-1637mg	14
	EC50	48h	Crustacea	2564mg/l	1
	EC50	96h	Algae or other aquatic plants	1562.44mg/L	4
	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96h	Fish	0.13-0.36mg/L	4
	EC50	72h	Algae or other aquatic plants	Algae or other aquatic plants 0.73mg/l	
sodium dichloroisocyanurate	EC50	48h	Crustacea	0.093-0.16mg/	_ 4
	NOEC(ECx)	96h	Fish	0.056mg/l	2
	EC:50	96h	Algae or other aquatic plants	655mg/l	2

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites. **DO NOT** discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
sodium carbonate	LOW	LOW
sodium sulfate	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
sodium carbonate	LOW (LogKOW = -0.4605)
sodium sulfate	LOW (LogKOW = -2.2002)

Mobility in soil

Ingredient	Mobility
sodium carbonate	HIGH (KOC = 1)
sodium sulfate	LOW (KOC = 6.124)

SECTION 13 Disposal considerations

Waste treatment methods	
Product / Packaging disposal	 Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: Reduction Recycling Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be

 DONOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible autority. FOR DISPOSAL OF SMALL QUANTITIES: Cautiously acidify a 3% solution or a suspension of the material to pH 2 with sulfuric acid. Gradually add a 50% excess of aqueous sodium bisulfite with stirring at room temperature. (Other reducers such as thiosulfate or ferrous salts may substitute; do NOT use carbon, sulfur or other strong reducing agents). An increase in temperature indicates reaction is taking place. If no reaction is observed on the addition of about 10% of the sodium bisulfite solution, initiate it by cautiously adding more acid. If manganese, chromium or molybdenum are present adjust the pH of the solution to 7 and treat with sulfide to precipitate for burial as a hazardous waste. Destroy excess sulfide, neutralise and flush the solution down the drain (subject to State and Local Regulation). [Sigma/Aldrich] Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / 	applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be
 It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. FOR DISPOSAL OF SMALL QUANTITES: Cautiously acidify a 3% solution or a suspension of the material to pH 2 with sulfuric acid. Gradually add a 50% excess of aqueous sodium bisulfite with stirring at room temperature. (Other reducers such as thiosulfate or ferrous salts may substitute; do NOT use carbon, sulfur or other strong reducing agents). An increase in temperature indicates reaction is taking place. If no reaction is observed on the addition of about 10% of the sodium bisulfite solution, initiate it by cautiously adding more acid. If manganese, chromium or molybdenum are present adjust the pH of the solution to 7 and treat with sulfide to precipitate for burial as a hazardous waste. Destroy excess sulfide, neutralise and flush the solution down the drain (subject to State and Local Regulation). [Sigma/Aldrich] Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / 	 DO NOT allow wash water from cleaning or process equipment to enter drains.
 In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. FOR DISPOSAL OF SMALL QUANTITES: Cautiously acidify a 3% solution or a suspension of the material to pH 2 with sulfuric acid. Gradually add a 50% excess of aqueous sodium bisulfite with stirring at room temperature. (Other reducers such as thiosulfate or ferrous salts may substitute; do NOT use carbon, sulfur or other strong reducing agents). An increase in temperature indicates reaction is taking place. If no reaction is observed on the addition of about 10% of the sodium bisulfite solution, initiate it by cautiously adding more acid. If manganese, chromium or molybdenum are present adjust the pH of the solution to 7 and treat with sulfide to precipitate for burial as a hazardous waste. Destroy excess sulfide, neutralise and flush the solution down the drain (subject to State and Local Regulation). [Sigma/Aldrich] Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / 	It may be necessary to collect all wash water for treatment before disposal.
 Where in doubt contact the responsible authority. FOR DISPOSAL OF SMALL QUANTITIES: Cautiously acidify a 3% solution or a suspension of the material to pH 2 with sulfuric acid. Gradually add a 50% excess of aqueous sodium bisulfite with stirring at room temperature. (Other reducers such as thiosulfate or ferrous salts may substitute; do NOT use carbon, sulfur or other strong reducing agents). An increase in temperature indicates reaction is taking place. If no reaction is observed on the addition of about 10% of the sodium bisulfite solution, initiate it by cautiously adding more acid. If manganese, chromium or molybdenum are present adjust the pH of the solution to 7 and treat with sulfide to precipitate for burial as a hazardous waste. Destroy excess sulfide, neutralise and flush the solution down the drain (subject to State and Local Regulation). [Sigma/Aldrich] Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / 	In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
 FOR DISPOSAL OF SMALL QUANTITIES: Cautiously acidify a 3% solution or a suspension of the material to pH 2 with sulfuric acid. Gradually add a 50% excess of aqueous sodium bisulfite with stirring at room temperature. (Other reducers such as thiosulfate or ferrous salts may substitute; do NOT use carbon, sulfur or other strong reducing agents). An increase in temperature indicates reaction is taking place. If no reaction is observed on the addition of about 10% of the sodium bisulfite solution, initiate it by cautiously adding more acid. If manganese, chromium or molybdenum are present adjust the pH of the solution to 7 and treat with sulfide to precipitate for burial as a hazardous waste. Destroy excess sulfide, neutralise and flush the solution down the drain (subject to State and Local Regulation). [Sigma/Aldrich] Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / 	Where in doubt contact the responsible authority.
 Cautiously acidify a 3% solution or a suspension of the material to pH 2 with sulfuric acid. Gradually add a 50% excess of aqueous sodium bisulfite with stirring at room temperature. (Other reducers such as thiosulfate or ferrous salts may substitute; do NOT use carbon, sulfur or other strong reducing agents). An increase in temperature indicates reaction is taking place. If no reaction is observed on the addition of about 10% of the solution to 7 and treat with sulfide to precipitate for burial as a hazardous waste. Destroy excess sulfide, neutralise and flush the solution down the drain (subject to State and Local Regulation). [Sigma/Aldrich] Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / 	FOR DISPOSAL OF SMALL QUANTITIES:
 Gradually add a 50% excess of aqueous sodium bisulfite with stirring at room temperature. (Other reducers such as thiosulfate or ferrous salts may substitute; do NOT use carbon, sulfur or other strong reducing agents). An increase in temperature indicates reaction is taking place. If no reaction is observed on the addition of about 10% of the sodium bisulfite solution, initiate it by caulously adding more acid. If manganese, chromium or molybdenum are present adjust the pH of the solution to 7 and treat with sulfide to precipitate for burial as a hazardous waste. Destroy excess sulfide, neutralise and flush the solution down the drain (subject to State and Local Regulation). [Sigma/Aldrich] Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / 	Cautiously acidify a 3% solution or a suspension of the material to pH 2 with sulfuric acid.
 place. If no reaction is observed on the addition of about 10% of the sodium bisulfite solution, initiate it by cautiously adding more acid. If manganese, chromium or molybdenum are present adjust the pH of the solution to 7 and treat with sulfide to precipitate for burial as a hazardous waste. Destroy excess sulfide, neutralise and flush the solution down the drain (subject to State and Local Regulation). [Sigma/Aldrich] Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / 	Gradually add a 50% excess of aqueous sodium bisulfite with stirring at room temperature. (Other reducers such as thiosulfate or ferrous salts may substitute; do NOT use carbon, sulfur or other strong reducing agents). An increase in temperature indicates reaction is taking
 If manganese, chromium or molybdenum are present adjust the pH of the solution to 7 and treat with sulfide to precipitate for burial as a hazardous waste. Destroy excess sulfide, neutralise and flush the solution down the drain (subject to State and Local Regulation). [Sigma/Aldrich] Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / 	place. If no reaction is observed on the addition of about 10% of the sodium bisulfite solution, initiate it by cautiously adding more acid.
 hazardous waste. Destroy excess sulfide, neutralise and flush the solution down the drain (subject to State and Local Regulation). [Sigma/Aldrich] Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / 	If manganese, chromium or molybdenum are present adjust the pH of the solution to 7 and treat with sulfide to precipitate for burial as a
 [Sigma/Aidrch] Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / 	hazardous waste. Destroy excess sulfide, neutralise and flush the solution down the drain (subject to State and Local Regulation).
 Recycle wnerever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / 	[Sigma/Aldrich]
 Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / 	Recycle wherever possible.
 Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / 	Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and /	Treat and neutralise at an approved treatment plant.
	Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and /
or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).	or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).
 Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed. 	Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

SECTION 14 Transport information

Labels Required	
Marine Pollutant	
HAZCHEM	2W

Land transport (ADG)

UN number	3098		
UN proper shipping name	OXIDISING LIQUID, CORROSIVE, N.O.S. (contains sodium perchlorate and sodium dichloroisocyanurate)		
Transport hazard class(es)	Class5.1Subrisk8		
Packing group	Ш		
Environmental hazard	Environmentally hazardous		
Special precautions for user	Special provisions 274 Limited quantity 1 L		

Air transport (ICAO-IATA / DGR)

UN number	3098			
UN proper shipping name	Oxidizing liquid, corrosive, n.o.s. * (contains sodium perchlorate and sodium dichloroisocyanurate)			
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	5.1 8 5C		
Packing group	П			
Environmental hazard	Environmentally hazardous			
Special precautions for user	Special provisions Cargo Only Packing Instructions Cargo Only Maximum Qty / Pack Passenger and Cargo Packing Instructions Passenger and Cargo Maximum Qty / Pack Passenger and Cargo Limited Quantity Packing Instructions		A3 A803 554 5 L 550 1 L Y540	
	Passenger and Cargo Limited Maximum Qty / Pack		0.5 L	

Sea transport (IMDG-Code / GGVSee)

UN number	3098	
UN proper shipping name	e OXIDIZING LIQUID, CORROSIVE, N.O.S. (contains sodium perchlorate and sodium dichloroisocyanurate)	

Transport hazard class(es)	IMDG Class IMDG Subrisk	5.1 8	
Packing group	1		
Environmental hazard	Marine Pollutant		
Special precautions for user	EMS Number Special provision Limited Quantitie	F-A, S-Q s 274 s 1 L	

Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
sodium carbonate	Not Available
sodium tripolyphosphate	Not Available
sodium perchlorate	Not Available
sodium sulfate	Not Available
sodium dichloroisocyanurate	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
sodium carbonate	Not Available
sodium tripolyphosphate	Not Available
sodium perchlorate	Not Available
sodium sulfate	Not Available
sodium dichloroisocyanurate	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

sodium carbonate is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 10 / Appendix C

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5 $\,$

sodium tripolyphosphate is found on the following regulatory lists

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 3 $\,$

sodium perchlorate is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

sodium sulfate is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

sodium dichloroisocyanurate is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 5 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 6 Australian Inventory of Industrial Chemicals (AIIC)

Australian Inventory of Industrial Chemicals (AIIC)

Australian Inventory of Industrial Chemicals (AIIC)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule $\mathbf{6}$

Australian Inventory of Industrial Chemicals (AIIC)

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (sodium carbonate; sodium tripolyphosphate; sodium perchlorate; sodium sulfate; sodium dichloroisocyanurate)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes

National Inventory	Status	
Mexico - INSQ	Yes	
Vietnam - NCI	Yes	
Russia - FBEPH	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

SECTION 16 Other information

Revision Date	14/09/2020		
Initial Date	14/09/2020		
SDS Version Summary			
Version	Date of Update	Sections Updated	
2.1	14/09/2020	Storage (suitable container)	

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit. IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.